



**Options:**  
 F = Filter and pump system  
 L1 = Lift 1x  
 L2 = Lift 2x

Technical Data	
Heater power	15.0kW 5 W/cm <sup>2</sup>
Voltage	400V 50Hz 3NAC
Fuse	3 x 25A
Mains connection	3L+N+PE L=1.5m(1cable)
Weight	2x1.25 kg
Capacity (max.)	2x1.0 kg
Capacity (rec.)	2x17-22 kg frozen chips
Capacity/hour	2x20-25 kg precooked
Oil capacity	2x7-9 liter

Avoid heat sources near the device when setting up. On the side and the backside must not be contact heat transfer by adjoining devices. It is permitted to close the existing air inlets.

*Technical subject to alteration!*

<b>Fryer VX 42 P</b> <b>Model VX 42 P</b>		Kienle GmbH Nellersstrasse 3 72691 Masselstein-Hardteln Telefon 0715 79 1020-0 Telefon 0715 79 1020-20 info@kienle-waerme.de info@kienle-waerme.de
Messstab: <b>1:10</b>	Version a <b>13.01.2010</b>	KIN
Blatt-Nr.: <b>ADM</b>	Gezeichnet <b>02.08.2020</b>	ccd
Blatt-Nr.: <b>1</b>	Zeichnung-Nr.: <b>206173</b>	Version <b>1</b>
Format: <b>A3</b>		

Das Urheberrecht an diesen Zeichnungen und allen Inhalten, die dem Empfänger persönlich zugesandt sind, verbleibt jederzeit unserer Firma. Ohne unsere schriftliche Genehmigung dürfen sie nicht kopiert oder veröffentlicht, auch niemals dritten Personen mitgeteilt oder zugänglich gemacht werden.

